

BUKTH.L4

Thermische isolatieklem L4

Thermal cond. Coëff. 0,033W/m.K

Stand. Uitv.

Elektrolytisch verzinkt



HD	Artikel	L mm	A mm	g mm	↔ mm	D mm	Max. bel. kN	M1	h mm	Con. type	Iso. d. G	Iso. L B	kg/stk	Stock	Eenh.
-	BUKTH.010L4	100	24	2		10,2	2	M8	5,3	A	18	55	0,110	1	STK
-	BUKTH.012L4	100	24	2		12	2	M8	5,3	A	18	55	0,110	1	STK
-	BUKTH.014L4	100	24	2		13,5	2	M8	5,3	A	18	55	0,110	1	STK
-	BUKTH.015L4	100	24	2		15	2	M8	5,3	A	18	55	0,120	1	STK
-	BUKTH.018L4	101	24	2		18	2	M8	5,3	A	18	55	0,120	1	STK
-	BUKTH.022L4	110	24	2		22	2	M8	5,3	A	19	55	0,140	1	STK
-	BUKTH.025L4	110	24	2		25	2	M8	5,3	A	19	55	0,140	1	STK
-	BUKTH.028L4	115	24	2		28	2	M8	5,3	A	20	55	0,170	1	STK
-	BUKTH.030L4	115	24	2		30	2	M8	5,3	A	20	55	0,170	1	STK
-	BUKTH.035L4	130	26	2,5		35	2,4	M10/M12	17,5	B	22	65	0,170	1	STK
-	BUKTH.038L4	136	26	2,5		38	2,4	M10/M12	17,5	B	22	65	0,170	1	STK
-	BUKTH.042L4	136	26	2,5		42,4	2,4	M10/M12	17,5	B	22	65	0,170	1	STK
-	BUKTH.045L4	136	26	2,5		44,5	2,4	M10/M12	17,5	B	21	65	0,230	1	STK
-	BUKTH.048L4	149	26	2,5		48,3	2,4	M10/M12	17,5	B	22	65	0,280	1	STK
-	BUKTH.054L4	155	26	2,5		54	2,4	M10/M12	17,5	B	22	65	0,290	1	STK
-	BUKTH.057L4	155	26	2,5		57	2,4	M10/M12	17,5	B	22	65	0,290	1	STK
-	BUKTH.060L4	170	26	2,5		60,3	2,4	M10/M12	17,5	B	23	75	0,330	1	STK
-	BUKTH.064L4	170	26	2,5		64	2,4	M10/M12	17,5	B	23	75	0,330	1	STK
-	BUKTH.070L4	170	26	2,5		70	2,4	M10/M12	17,5	B	23	75	0,330	1	STK
-	BUKTH.076L4	176	26	2,5		76,1	2,4	M10/M12	17,5	B	23	85	0,380	1	STK
-	BUKTH.080L4	183	26	2,5		80	2,4	M10/M12	17,5	B	23	85	0,410	1	STK
-	BUKTH.089L4	194	26	2,5		88,9	2,4	M10/M12	17,5	B	24	100	0,450	1	STK
-	BUKTH.102L4	220	35	3		101,6	3,9	M10/M12	25	C	25	100	0,740	1	STK
-	BUKTH.108L4	235	35	3		108	3,9	M10/M12	25	C	24	100	0,740	1	STK
-	BUKTH.114L4	235	35	3		114,3	3,9	M10/M12	25	C	24	115	0,770	1	STK
-	BUKTH.125L4	235	35	3		125	3,9	M10/M12	25	C	24	115	0,790	1	STK
-	BUKTH.133L4	261	35	3		133	3,9	M10/M12	25	C	25	115	0,850	1	STK
-	BUKTH.140L4	252	35	3		139,7	3,9	M10/M12	25	C	25	115	0,850	1	STK
-	BUKTH.160L4	284	35	3		160	3,9	M10/M12	25	C	25	115	1,010	1	STK
-	BUKTH.165L4	305	35	3		165,1	3,9	M12/M16	25	C	25	125	1,100	1	STK
-	BUKTH.168L4	305	35	3		168,3	3,9	M12/M16	25	C	25	125	1,100	1	STK
-	BUKTH.200L4	334	35	3		200	3,9	M12/M16	25	C	27	170	1,400	1	STK
-	BUKTH.216L4	376	35	4		216	4,5	M12/M16	26	C	25	165	1,890	1	STK
-	BUKTH.219L4	376	35	4		219,1	4,5	M12/M16	26	C	25	165	1,890	1	STK

HD	Artikel	L mm	A mm	g mm	↔ mm	D mm	Max. bel. kN	M1	h mm	Con. type	Iso. d. G	Iso. L B	kg/stk		Stock	Eenh.
-	BUKTH.250L4	420	35	4		250	4,5	M12/M16	26	C	27	170	2,010	1		STK
-	BUKTH.267L4	420	35	4		267	4,5	M12/M16	26	C	25	165	2,160	1		STK
-	BUKTH.273L4	428	35	4		273	4,5	M12/M16	26	C	25	165	2,210	1		STK

Met kruiskopbouten M6 (tot 089), met zeskantbout M8 (vanaf 101).

Temperatuurbereik: -50/+110°C.

Isolatiemateriaal: Dikte: 18-27 mm.

PET inserts (100kg/m³) in schuimrubber. Extra beschermende buitenschil van 0,8mm aluminium.