

BUKEX.R

Buisklem EXPERT met inleg

Met EPDM inleg.

Stand. Uitv.

Elektrolytisch verzinkt



HD	Artikel	L mm	A mm	g mm	↔ mm	D mm	Max. bel. kN	M1	h mm	Con. type	kg/stk	📦	Stock	Eenh.
-	BUKEX.016R	63	20	2		16-20	2	M8	5,3	A	0,060	100		STK
HD	BUKEX.020R	70	20	2		20-24	2	M8	5,3	A	0,060	100		STK
HD	BUKEX.026R	75	20	2		26-30	2	M8	5,3	A	0,070	100		STK
HD	BUKEX.034R	90	24	2		34-39	2	M8	5,3	A	0,100	50		STK
HD	BUKEX.041R	100	24	2		41-46	2	M8	5,3	A	0,110	50		STK
HD	BUKEX.048R	101	24	2		48-53	2	M8	5,3	A	0,120	50		STK
HD	BUKEX.052R	110	24	2		52-57	2	M8	5,3	A	0,130	50		STK
HD	BUKEX.059R	115	24	2		59-64	2	M8	5,3	A	0,130	50		STK
HD	BUKEX.074R	136	26	2,5		74-79	2,4	M10/M12	17,5	B	0,220	25		STK
-	BUKEX.078R	149	26	2,5		78-84	2,4	M10/M12	17,5	B	0,250	25		STK
HD	BUKEX.085R	154	26	2,5		85-91	2,4	M10/M12	17,5	B	0,260	25		STK
-	BUKEX.102R	170	26	2,5		102-108	2,4	M10/M12	17,5	B	0,280	25		STK
HD	BUKEX.107R	176	26	2,5		107-113	2,4	M10/M12	17,5	B	0,284	25		STK
HD	BUKEX.112R	176	26	2,5		112-118	2,4	M10/M12	17,5	B	0,310	25		STK
-	BUKEX.124R	194	26	2,5		124-131	2,4	M10/M12	17,5	B	0,340	25		STK
HD	BUKEX.130R	194	26	2,5		130-138	2,4	M10/M12	17,5	B	0,350	20		STK
HD	BUKEX.141R	221	35	3		141-148	3,9	M10/M12	25	C	0,610	10		STK
HD	BUKEX.158R	235	35	3		158-166	3,9	M10/M12	25	C	0,630	10		STK
HD	BUKEX.164R	236	35	3		164-172	3,9	M10/M12	25	C	0,650	10		STK
HD	BUKEX.200R	286	35	3		200-208	3,9	M10/M12	25	C	0,820	10		STK
-	BUKEX.210R	300	35	3		206-214	3,9	M12/M16	25	C	0,850	10		STK
HD	BUKEX.214R	305	35	3		214-222	3,9	M12/M16	25	C	0,870	5		STK
HD	BUKEX.244R	334	35	3		244-252	3,9	M12/M16	25	C	0,940	5		STK
HD	BUKEX.264R	376	35	4		264-273	4,5	M12/M16	26	C	1,420	5		STK
-	BUKEX.307R	420	35	4		307-316	4,5	M12/M16	26	C	1,580	5		STK
-	BUKEX.317R	428	35	4		317-326	4,5	M12/M16	26	C	1,620	5		STK
-	BUKEX.355R	423	35	4		345-357	4,5	M12/M16	26	C	1,592	5		STK
-	BUKEX.395R	467	35	4		395-404	4,5	M12/M16	26	C	1,840	5		STK
-	BUKEX.495R	569	35	4		495-504	4,5	M12/M16	26	C	2,220	5		STK

Te bestellen per volle verpakking.

Met kruiskopbouten (tot 130), met zeskantbout (>130).

Temperatuurbereik: -40/+120°C.

Silicone inleg voor temperatuurbereik -60/+250°C verkrijgbaar op aanvraag.

Geluidsisolerend volgens DIN 4109.