

# BTFCL

## Horizontale bocht 90°



Gesloten bodem  
Boordomslag

Radius: 250 mm

Stand. Uitv.

Sendzimir


Mat. Opt.

Hot-Dip


Mat. Opt. PE

Poedercoating

### Te bevestigen met:



Koppelplaat  
V85.200



Koppelplaat  
V60.200



Koppelplaat  
V35.200

HD	Artikel	↕ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
HD	<b>BTFCL60.100</b>	60	100	2		3,000	1		STK
HD	<b>BTFCL60.150</b>	60	150	2		3,830	1		STK
HD	<b>BTFCL60.200</b>	60	200	2		4,730	1		STK
HD	<b>BTFCL60.250</b>	60	250	2		5,710	1		STK
HD	<b>BTFCL60.300</b>	60	300	2		6,740	1		STK
HD	<b>BTFCL85.100</b>	85	100	2		3,630	1		STK
HD	<b>BTFCL85.150</b>	85	150	2		4,500	1		STK
HD	<b>BTFCL85.200</b>	85	200	2		5,430	1		STK
HD	<b>BTFCL85.250</b>	85	250	2		6,430	1		STK
HD	<b>BTFCL85.300</b>	85	300	2		7,490	1		STK
HD	<b>BTFCL110.150</b>	110	150	2		5,150	1		STK
HD	<b>BTFCL110.200</b>	110	200	2		6,120	1		STK
HD	<b>BTFCL110.250</b>	110	250	2		7,150	1		STK
HD	<b>BTFCL110.300</b>	110	300	2		8,240	1		STK