



Bari DL LED 155 mm 21W 4000K

BASIC DATA

Code	DG002.1166.840.A000 PX4089478
EAN	5907769498442
Weight	1,00 kg

Application: corridors, conference rooms, receptions, waiting rooms

Category of luminaire: downlight

MECHANICAL DATA

Type of installation	Recessed
Housing material	Die cast aluminum

OPTICAL DATA

Diffuser material	Transparent glass
Reflector	High gloss

ELECTRICAL DATA

Light source	LED
Luminaire power	21W
Number of light sources	1
Light source power	21W
Voltage rating	220 ... 240 V
Light source included	yes

INFORMATION



Colour	White
Operating temperature range	0 ... 35 °C
Rotated model	No

LIGHT DATA

Light source luminous flux	2830 lm
Luminaire luminous flux	2370lm
Light source luminous efficacy	157 lm/W
Luminaire's luminous efficacy	113 lm/W
Luminaire's luminous efficiency	84 %
Light colour	White
Color rendering index	84
Light distribution	DI
Class of luminaire	I
Beam angle	45 °
Light output degradation	B10
Lumen maintenance	L90
Lifetime	> 60000 h
MacAdam	SDCM 3
Lamp Lumen Maintenance Factor (after 60 000h)	91 %
Colour temperature	4000K

CERTIFICATES

Degree of protection (IP)	IP44
Class of protection	I
CE	yes
PZH	yes
HACCP+	yes
EAC	yes



DIMENSIONS

H [mm]	F [mm]	G [mm]	D [mm]	E [mm]
105	155	113	105	115

H = Height / Depth | F = Outer diameter | G = Inner diameter | D = Installation width | E = Installation depth