

KBSI60


Kabelbaan ineenschuifbaar

Ineenschuifbare uiteinden
Langs- en dwarsperforaties
Boordomslag



Stand. Uitv.	Sendzimir
Mat. Opt.	Hot-Dip
Mat. Opt. PE	Poedercoating

Te bevestigen met:



HD Artikel	↑ mm	↔ mm	→ ← mm	↔ mm	kg/m	📦	Stock	Eenh.
HD KBSI60.075.100	60	75	1	3000	1,400	60	X	M
- KBSI60.075.125	60	75	1,25	3000	1,750	60	X	M
HD KBSI60.100.075	60	100	0,75	3000	1,170	60	X	M
HD KBSI60.100.100	60	100	1	3000	1,560	60	X	M
- KBSI60.100.125	60	100	1,25	3000	1,950	60	X	M
HD KBSI60.150.075	60	150	0,75	3000	1,420	30	X	M
HD KBSI60.150.100	60	150	1	3000	1,890	30	X	M
- KBSI60.150.125	60	150	1,25	3000	2,360	30	X	M
HD KBSI60.200.075	60	200	0,75	3000	1,660	30	X	M
HD KBSI60.200.100	60	200	1	3000	2,220	30	X	M
- KBSI60.200.125	60	200	1,25	3000	2,770	30	X	M
HD KBSI60.300.075	60	300	0,75	3000	2,150	30	X	M
HD KBSI60.300.100	60	300	1	3000	2,870	30	X	M
- KBSI60.300.125	60	300	1,25	3000	3,580	30	X	M
HD KBSI60.400.100	60	400	1	3000	3,520	30	X	M

Zelfborgende moer en kraagbout
VMK

