

BUKTH.L6

Thermische isolatieklem L6

Thermal cond. Coëff. 0,033W/m.K

Stand. Uitv.

Elektrolytisch verzinkt



HD	Artikel	L mm	A mm	g mm	↔ mm	D mm	Max. bel. kN	M1	h mm	Con. type	Iso. d. G	Iso. L B	kg/stk	Stock	Eenh.
-	BUKTH.015L6	130	26	2,5		15	2,15	M10/M12	17,5	B	30	75	0,240	1	STK
-	BUKTH.018L6	130	26	2,5		18	2,15	M10/M12	17,5	B	30	75	0,240	1	STK
-	BUKTH.022L6	136	26	2,5		22	2,15	M10/M12	17,5	B	30	75	0,270	1	STK
-	BUKTH.025L6	149	26	2,5		25	2,15	M10/M12	17,5	B	30	75	0,280	1	STK
-	BUKTH.028L6	149	26	2,5		28	2,15	M10/M12	17,5	B	32	75	0,290	1	STK
-	BUKTH.030L6	145	26	2,5		30	2,15	M10/M12	17,5	B	33	75	0,300	1	STK
-	BUKTH.035L6	145	26	2,5		35	2,15	M10/M12	17,5	B	35	85	0,300	1	STK
-	BUKTH.038L6	170	26	2,5		38	2,15	M10/M12	17,5	B	35	85	0,310	1	STK
-	BUKTH.042L6	167	26	2,5		42,4	2,15	M10/M12	17,5	B	35	85	0,350	1	STK
-	BUKTH.045L6	167	26	2,5		44,5	2,15	M10/M12	17,5	B	35	85	0,350	1	STK
-	BUKTH.048L6	176	26	2,5		48,3	2,15	M10/M12	17,5	B	35	85	0,380	1	STK
-	BUKTH.054L6	183	26	2,5		54	2,15	M10/M12	17,5	B	36	85	0,400	1	STK
-	BUKTH.057L6	194	26	2,5		57	2,15	M10/M12	17,5	B	36	85	0,410	1	STK
-	BUKTH.060L6	194	26	2,5		60,3	2,15	M10/M12	17,5	B	37	100	0,470	1	STK
-	BUKTH.064L6	194	26	2,5		64	2,15	M10/M12	17,5	B	37	100	0,530	1	STK
-	BUKTH.070L6	194	26	2,5		70	2,15	M10/M12	17,5	B	37	100	0,540	1	STK
-	BUKTH.076L6	220	35	3		76,1	3,9	M10/M12	25	C	38	115	0,820	1	STK
-	BUKTH.080L6	235	35	3		80	3,9	M10/M12	25	C	38	115	0,860	1	STK
-	BUKTH.089L6	235	35	3		88,9	3,9	M10/M12	25	C	39	125	0,890	1	STK
-	BUKTH.102L6	261	35	3		101,6	3,9	M10/M12	25	C	40	125	0,910	1	STK
-	BUKTH.108L6	252	35	3		108	3,9	M10/M12	25	C	40	125	0,950	1	STK
-	BUKTH.114L6	284	35	3		114,3	3,9	M10/M12	25	C	41	145	1,140	1	STK
-	BUKTH.125L6	284	35	3		125	3,9	M10/M12	25	C	41	145	1,200	1	STK
-	BUKTH.133L6	305	35	3		133	3,9	M12/M16	25	C	43	145	1,230	1	STK
-	BUKTH.140L6	305	35	3		139,7	3,9	M12/M16	25	C	43	145	1,250	1	STK
-	BUKTH.160L6	334	35	3		160	3,9	M12/M16	25	C	44	145	1,420	1	STK
-	BUKTH.165L6	334	35	3		165,1	3,9	M12/M16	25	C	45	165	1,550	1	STK
-	BUKTH.168L6	334	35	3		168,3	3,9	M12/M16	25	C	45	165	1,550	1	STK
-	BUKTH.200L6	420	35	4		200	4,5	M12/M16	26	C	50	215	2,200	1	STK
-	BUKTH.216L6	420	35	4		216	4,5	M12/M16	26	C	50	210	2,690	1	STK
-	BUKTH.219L6	428	35	4		219,1	4,5	M12/M16	26	C	50	210	2,710	1	STK

Met kruiskopbouten M6 (tot 070), met zeskantbout M8 (vanaf 076), M12 (vanaf 200).

Temperatuurbereik: -50/+110°C.

Isolatiemateriaal: Dikte: 30-50 mm.

PET inserts (100kg/m³) in schuimrubber. Extra beschermende buitenschil van 0,8mm aluminium.