



# KLLX

## Kruisstuk voor KLL



### Te bevestigen met:



Zelfborgende moer en bout  
VM

Radius: 300 mm

Stand. Uitv.

Sendzimir

Mat. Opt.

Hot-Dip

Mat. Opt. PE

Poedercoating

|   | 150  | 200  | 300  | 400  | 500  | 600  |
|---|------|------|------|------|------|------|
| A | 1021 | 1071 | 1171 | 1271 | 1371 | 1471 |

| HD | Artikel            | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Stock | Eenh. |
|----|--------------------|---------|---------|------------|---------|--------|---|-------|-------|
| HD | <b>KLLX60.150</b>  | 60      | 141     |            |         | 3,131  | 1 |       | STK   |
| HD | <b>KLLX60.200</b>  | 60      | 191     |            |         | 3,232  | 1 |       | STK   |
| HD | <b>KLLX60.300</b>  | 60      | 291     |            |         | 4,421  | 1 |       | STK   |
| HD | <b>KLLX60.400</b>  | 60      | 391     |            |         | 4,875  | 1 |       | STK   |
| HD | <b>KLLX60.450</b>  | 60      | 443     |            |         | 5,102  | 1 |       | STK   |
| HD | <b>KLLX60.500</b>  | 60      | 491     |            |         | 5,329  | 1 |       | STK   |
| HD | <b>KLLX60.600</b>  | 60      | 591     |            |         | 5,782  | 1 |       | STK   |
| HD | <b>KLLX85.150</b>  | 85      | 145     |            |         | 3,525  | 1 |       | STK   |
| HD | <b>KLLX85.200</b>  | 85      | 195     |            |         | 4,032  | 1 |       | STK   |
| HD | <b>KLLX85.300</b>  | 85      | 295     |            |         | 5,221  | 1 |       | STK   |
| HD | <b>KLLX85.400</b>  | 85      | 395     |            |         | 5,675  | 1 |       | STK   |
| HD | <b>KLLX85.450</b>  | 85      | 445     |            |         | 5,902  | 1 |       | STK   |
| HD | <b>KLLX85.500</b>  | 85      | 495     |            |         | 6,129  | 1 |       | STK   |
| HD | <b>KLLX85.600</b>  | 85      | 595     |            |         | 6,582  | 1 |       | STK   |
| HD | <b>KLLX110.150</b> | 110     | 145     |            |         | 4,537  | 1 |       | STK   |
| HD | <b>KLLX110.200</b> | 110     | 195     |            |         | 4,796  | 1 |       | STK   |
| HD | <b>KLLX110.300</b> | 110     | 295     |            |         | 5,985  | 1 |       | STK   |
| HD | <b>KLLX110.400</b> | 110     | 395     |            |         | 6,439  | 1 |       | STK   |
| HD | <b>KLLX110.450</b> | 110     | 445     |            |         | 6,666  | 1 |       | STK   |
| HD | <b>KLLX110.500</b> | 110     | 495     |            |         | 6,893  | 1 |       | STK   |
| HD | <b>KLLX110.600</b> | 110     | 595     |            |         | 7,346  | 1 |       | STK   |

Minimum aantal bouten en moeren VM6.10: 16 stuks.