



Bari Q LED 225mm 17W 4000K

BASIC DATA

Code	EU003.1111.840.A000
EAN	5904312956374

Application: corridors, conference rooms, receptions, waiting rooms

Category of luminaire: downlight

OPTICAL DATA

Louver/ shutter	OPAL
Diffuser colour	White
Diffuser material	Opal/mat plastic

ELECTRICAL DATA

Light source	LED
Luminaire power	17W
Number of light sources	1
Type of equipment	AC
Voltage rating	220 ... 240 V
Light source included	yes

INFORMATION


Colour	White
Info	225mm

LIGHT DATA

Luminaire luminous flux	2460lm
Luminaire's luminous efficacy	145 lm/W
Light colour	White
Light distribution	DI
Light output degradation	B10
Lumen maintenance	L70
Lifetime	> 50000 h
Colour temperature	4000K

CERTIFICATES


Degree of protection (IP)	IP44
Degree of protection (IP) /top/	IP20
Class of protection	II
Light source protection	yes
CE	yes
PZH	yes
HACCP+	yes



DIMENSIONS

H [mm]	F [mm]	K [mm]	J [mm]
40	225	15	15

H = Height / Depth | F = Outer diameter | K = Additional dimension | J = Additional dimension



ACCESSORIES

Electric elements



FS032.11.1500.A
FS032.11.1500.D
FS032.22.1500.A
FS032.22.1500.D
FS032.33.1500.A
FS032.33.1500.D

Bari Q LED central suspension 3x

Structural elements



FL030.11.0225

BARI Q LED Surface mounting housing IP20



FL043.11.0228
FL043.22.0228
FL043.33.0228

BARI Q LED Surface mounting housing IP44